

Bijlard MS Multi Primer Floor



PRODUCT DESCRIPTION

MS MULTI PRIMER FLOOR is a 1-component primer based on MSP.

APPLICATION

MS MULTI PRIMER FLOOR is for sealing and/or reinforcing highly absorbent and solid or silting subfloors. Can be bonded directly with PU2K or MS-FLOOR. Suitable for underfloor heating. Can be used as a barrier against residual moisture in concrete floors and cement floors up to 4 CM% (with underfloor heating a maximum of 3 CM%).

The subfloor must meet the requirements of ATV DIN 18 365 (Requirements for the subfloor) resp. ATV DIN 18 356 (Installation and maintenance instructions). The subfloor must be clean and free of solvents, firm and free of cracks. Old floor coverings and loose adhesive and leveling compound must be completely removed mechanically. Brush and vacuum new concrete and cement screeds, remove construction residues. Always sand anhydrite floors (grain size 16) and vacuum. Sand hard stone and tile floors or clean thoroughly with CITRONEL. Maximum CM moisture content for the following applications are: Concrete and cement screed inside, on insulation or separating layer, 2.0 CM%. Indoor anhydrite floors, without underfloor heating, 0.5 CM%. Anhydrite floors inside, with underfloor heating, 0.3 CM%.

PROCESSING

The subfloor must be clean, dry, crack-free, tensile and compressive resistant. Shake the packaging well before use and then apply the product with a velor roller apply evenly and thinly. If the surface does not show any irregularities, a lambskin roller can be used. Avoid puddles. When using BIJLARD EGALINE 10A, a second layer of MS MULT PRIMER FLOOR must be applied and finished with fire-dried quartz sand (see doc. sheet BIJLARD EGALINE 10A).

CHARACTERISTICS

Universally applicable
Very low consumption
For use with underfloor heating

BIJLARD®
PROFESSIONAL ADHESIVES

TECHNICAL INFORMATION

Basic raw material : MSP
Color : transparent
Processing temperature : + 10° C to + 30° C
Specific gravity : 1.0 kg/m³
Consumption : approx. 6-10 m²/kilo
Curing time : 90 minutes

CLEANING

Clean tools with CLEANER CS60©

SHELF LIFE

MS MULTI PRIMER FLOOR has a shelf life of 12 months after production in unopened packaging in a cool, frost-free place.

PACKAGING

can 5 kg

Our processing recommendations are based on extensive research. Due to the wide variety of materials and conditions under which gluing takes place, we cannot accept liability for the results obtained and/or any damage that may result from the use of the product. We are at your disposal with advice.

BIJLARD®
PROFESSIONAL ADHESIVES