

BIJLARD CARPETSPRAY 5920



PRODUCT DESCRIPTION

Is a spray that prevents woven carpets, sisal, coco, carpet-tiles, underpadding, clothing, felt, carton etc. from fraying while cutting.

DIRECTIONS FOR USE

- Shake can well before use.
- Mark cutting line on the backing of the material.
- Spray in widths of approx. 4 cm. holding the can at 10 cm distance.
- Spray generously in order to saturate the backing up to the pile anchoring.
- Allow the spray to dry completely before cutting.
- Carpet spray (anti-fraying spray) dries transparently and non-sticky.
- Thick coco-mats must also be sprayed from the top side. Spray from a short distance in between the fibres, bending the material backwards at the cutting line.
- To keep nozzle clear after use, hold the aerosol upside down and push button until no liquid comes out anymore.
- Tools can be cleaned with acetone.

TECHNICAL INFORMATION

Based on : PVAc-rubber in solution.

Specific weight : 0.91 ± 0.5 Kg/L.

Solids contents : 38.5 ± 0.5 %.

Physical form : aerosol.

Viscosity : 50 - 100 mPa.s (+20°C).

Colour : transparent.

Drying time : approx. 2 - 5 min. (+20°C).

Propellant : propane/butane; No CFK.

SHELF LIFE

1 year +20°C in unopened can.

CLEANING

VERDUNNER.

PACKAGING

500 ml aerosol.

Our processing advice is based on extensive research and practical experience. We can accept no liability for the results obtained and / or any damage resulting from the use of this product because of the wide range of materials and circumstances in which the glue is used. Nevertheless we would be pleased to advise you.

BIJLARD®
PROFESSIONAL ADHESIVES